LaJuana S. Wilcher Secretary

# **AIR QUALITY PERMIT**

Ernie Fletcher

Governor

Issued under 401 KAR 52:020 Title V Permits for Major Sources



Commonwealth of Kentucky
Environmental and Public Protection Cabinet
Department for Environmental Protection
Division for Air Quality
803 Schenkel Lane
Frankfort, Kentucky 40601
(502) 573-3382

Permittee Name: SGL Carbon, LLC

Mailing Address: 2320 Myron Cory Drive, Hickman, KY 42050

is authorized to operate a graphite electrode manufacturing facility.

Source Name: Same as above Mailing Address: Same as above Source Location: Same as above

**KYEIS ID #:** 21-075-00001 SIC Code: 3624 AI Number: 1440 County: Fulton

**Activity #: APE20050001** 

Permit Number: V-01-023 R1 Permit Type: TITLE V

Regional Office: Paducah Application Completion Date: 04/04/2005

4500 Clark River Road Issuance Date: January 30, 2003 Paducah, KY 42003 Revision Date: June 6, 2005 Expiration Date: January 30, 2008

John S. Lyons, Director

John S. Lyons, Director Division for Air Quality

**DEP7001 (6-97)** *Revised: 07/10/03* 

# **Title V-Construction/Operating Permit**

SGL Carbon LLC Subject Item Inventory

Activity ID No.: APE20050001

# **Subject Item Inventory:**

ID	Designation	Description
AIOO1440	Source	General Requirements
COMB1	008	INSIGNIFICANT BOILERS
	l	<sup>1</sup> 1. 6.1 mmBtu/hr
		2. 6.1 mmBtu/hr
		3. 5.23 mmBtu/hr
		4. 2.41 mmBtu/hr
EQPT1	001	COKE UNLOADING
	l	Process Unit: Hopper
		Max Oper Rate: 25 tons/hr
		Control Device: none
		Installation Date: January 1, 1990
EQPT2	002	PARTICLE SCREENING
	I	Process Unit: Morgensen Screen (small fraction)
		Max Oper Rate: 14 tons/hr
		Control Device: Wheelabrator Dust Collector
		Installation Date: June 21, 1995
EQPT3	004	MIXING/EXTRUSION
	I	Process Unit: Eirich Mixer/Eisen Mann RTO
		Max Oper Rate: 25 tons/hr
		Control Device: Thermal Oxidizer and Rotary Wet Scrubber
	i	Installation Date: June 21, 1995
EQPT4	005	BAKING CONVEYOR SYSTEM
	I	Process Unit: Dump Hopper/VibratingScreens/Rotex Screener
		Max Oper Rate: 20/8/16 tons/hr
		Control Device: None
	1	Installation Date: January 1, 1990
EQPT5	006	HARGRAF MACHINE
	1	Process Unit: Hargraf Cleaning
		Max Oper Rate: 15 tons/hr
		Control Device: Baghouse with Polyester Filter Bags
		Installation Date: July 1, 1969

# **Title V-Construction/Operating Permit**

SGL Carbon LLC Subject Item Inventory

Activity ID No.: APE20050001

ID	Designation	Description
EQPT6	007	RING BAKE FURNACE Process Unit: Electrode Bake/Natural Gas Max Oper Rate: 2.98 tons/hr Control Device: Electrostatic Precipitators Modification Date: 2001
STOR1	003	COAL TAR PITCH TANKS Process Unit: Storage Tanks Max Oper Rate: 285 gal/hr Applicable Reg:40 CFR 60 Subpart Kb

# **Subject Item Groups:**

ID	Description	Components
GACT1	Insignificant Activities	EQPT7 Insignificant
		4) Silos Screw Conveyor
		5) Vibrator Feeder
		6) Jaw Crusher
		7) South Silo
		8) North Silo
		9) Fines Bin
		10) A-Discharge Feeder
		11) B-Discharge Feeder
		12) Vacuum

# Title V-Construction/Operating Permit SGL Carbon LLC

SGL Carbon LLC Subject Item Inventory

Activity ID No.: APE20050001

ID	Description	Components
GACT1	Insignificant Activities	EQPT9 Insignificant
		16) Fines to Silo Conveyor (2)
		17) Fines to Silo Conveyor
		18) Surge Hopper (Small)
		19) Surge Hopper (Large)
		20) Belt Feeder
		21) Screw Conveyor
		22) Bucket Elevator
		Coke Unloading:
		1) Hopper Feeder
		2) Bucket Elevator
		Tanks:
		1) Extrusion Oil
		Mixing/ Extrusion:
		1) Natural gas usage
		Baking System:
		1) Truck hopper
		2) Belt Conveyor
		3) Elevator Conveyor

# Title V-Construction/Operating Permit SGL Carbon LLC

SGL Carbon LLC Subject Item Inventory

Activity ID No.: APE20050001

ID	Description	Components
GACT1	Insignificant Activities	EQPT8 Insignifcant Activities
		Particle Screening
		1) Roof Screw Conveyor
		2) Screen Presizing
		3) Screen (Large)
		4) 6 Fine Particle Bins
		5) 6 Coarse Particle Bins
		6) 6 Fine Particle Bin Feeder
		7) 6 Coarse Particle Bin Feeder
		8) Small Particle Scale
		9) Large Particle Scale
		10) Vibrate Conveyor #2
		11) Vibrate Conveyor #1
		12) Fines to Silo Conveyor
		13) Fines Up Conveyor
		14) Fines to Silo Conveyor
		15) Fines to Raw Conveyor
GACT2	Fugitive Emissions	EQPT4 BAKING CONVEYOR SYSTEM
		Process Unit: Dump Hopper/VibratingScreens/Rotex Screener
		Max Oper Rate: 20/8/16 tons/hr
		Control Device: None
		Installation Date: January 1, 1990
		EQPT1 COKE UNLOADING
		Process Unit: Hopper
		Max Oper Rate: 25 tons/hr
		Control Device: none
		Installation Date: January 1, 1990

KEY	
ACTV = Activity	AIOO = Agency Interest
AREA = Area	COMB = Combustion
EQPT = Equipment	MNPT = Monitoring Point
PERS = Personnel	PORT = Transport

# **Title V-Construction/Operating Permit**

SGL Carbon LLC Subject Item Inventory

Activity ID No.: APE20050001

**KEY** 

STOR = Storage STRC = Structure

TRMT = Treatment

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 1 of 20

### Submittal/Action Requirements:

#### No. Condition

Condition

#### S-1 SEMIANNUAL REPORTS:

The permittee shall submit report(s): Due semiannually, by the 30th of January and July to the Regional Office listed on the front of this permit at least every six (6) months during the life of this permit. This report shall be a summary of any monitoring required by this permit, other than continuous emission or opacity monitors. For emission units that had not yet begun construction, were still under construction, or which had not commenced operation at the end of the 6-month period covered by the report and are subject to monitoring requirements in this permit, the report shall indicate that no monitoring was performed during the previous six months because the emission unit was not in operation. All reports shall be certified by a responsible official. All deviations from permit requirements shall be clearly identified in the reports. [401 KAR 52:040 Section 21]

#### S-2 COMPLIANCE CERTIFICATION:

The permittee shall certify compliance with the terms and conditions contained in this permit and shall submit compliance certification: Due annually, by the 30th of January to the Regional Office listed on the front of this permit. Compliance Certification Form (DEP 7007CC) (or an approved alternative) shall be used in accordance with the following requirements:

- a. Identification of the term or condition;
- b. Compliance status of each term or condition of the permit;
- c. Whether compliance was continuous or intermittent;
- d. The method used for determining the compliance status for the source, currently and over the reporting period, and
- e. For emission units that had not yet begun construction, were still under construction, or which had not commenced operation at the end of the 12-month period covered by the annual compliance certification, the permittee shall indicate that the unit is not in operation and that compliance with any applicable requirements will be demonstrated within the timeframes specified in the permit.
- f. The certification shall be postmarked by January 30th of each year. Annual compliance certifications should be mailed to the Regional Office listed on the front of this permit and the following address:

Division for Air Quality Central Files 803 Schenkel Lane Frankfort, KY 40601. [401 KAR 52:040 Section 19]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Submittal/Action Requirements:

110.	Condition
No.	Condition
Condition	

#### S-3 NOTIFICATION:

The following information shall be reported:

- a. Date when construction commenced, (See Requirement H1.).
- b. Start-up date of each of the affected facilities listed on this permit.
- c. Date when maximum production rate was achieved, (See Requirement H2.). The permittee shall submit information: Due within 30 days after construction commencement or within 15 days following start-up and attainment of maximum production rate, or within 15 days following the issuance date of this permit, whichever is later, to the Regional Office listed on the front of this permit, with a copy to the Division's Frankfort Central Office. [401 KAR 59:005 Section 3(1)]

#### S-4 PERFORMANCE TESTS:

This permit shall allow operation for compliance demonstration of the affected facilities listed herein. However, within 60 days after the issuance date of this permit or the date of achieving the maximum production rate at which the affected facilities will be operated, whichever is later, but no later than 180 days after initial start-up of such facilities, or the issuance date of this permit, whichever is later, the owner or operator shall demonstrate compliance to a duly authorized representative of the Division. [401 KAR 59:005 Section 2(1)]. The permittee shall complete and submit Compliance Test Protocol (Form DEP 6027): Due at least 30 days prior to performance/emissions test to the Regional Office listed on the front of this permit [Policy Manual of the Division of Air Quality, Section VII 2.(1)][401 KAR 50:016 Section 1(1)]. The protocol form shall be utilized by the Division to determine if a pretest meeting is required. The Division shall be notified of the actual test date at least 10 working days prior to the test(s). [401 KAR 50:045 Section 5]

#### S-5 PERFORMANCE TEST NOTICE AND REPORT:

Pursuant to Section VII 2.(1) of the policy manual of the Division for Air Quality as referenced by 401 KAR 50:016, Section 1.(1), at least one month prior to the date of any required performance test(s), the permittee shall complete and return a Compliance Test Protocol (Form DEP 6027) to the Division's Frankfort Central Office. Pursuant to 401 KAR 50:045, Section 5, the Division shall be notified of the actual test date at least ten (10) days prior to the test.

For any performance test(s) required by this permit, the permittee shall submit performance/emission test results: Due within 45 days of the completion of the fieldwork to the Division. [Policy Manual of the Division for Air Quality, Section VII.3] [401 KAR 50:016 Section 1(1)]

Page 2 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 3 of 20

Submittal/Action Requirements:

Condition No.	Condition
S-6	PERMIT EXPIRATION AND REAPPLICATION REQUIREMENTS:
	This permit shall remain in effect for a fixed term of ten (10) years following the original date of issue. Permit expiration shall terminate the source's right to operate unless a timely and complete renewal application has been submitted to the Division. The permittee shall submit permit application for renewal: Due 180 calendar days before permit expiration date to the Division. Upon a timely and complete submittal, the authorization to operate within the terms and conditions of this permit, including any permit shield, shall remain in effect beyond the expiration date, until the renewal permit is issued or denied by the Division. [401 KAR 52:040 Section 15]

# Narrative Requirements:

Condition	
No.	Condition
T-1	SECTION A. PERMIT AUTHORIZATION. [401 KAR 52:040]
T-2	A1. Pursuant to a duly submitted application, the Kentucky Division for Air Quality hereby authorizes the construction and operation of the equipment described herein in accordance with the terms and conditions of this permit. This permit has been issued under the provisions of Kentucky Revised Statutes Chapter 224 and regulations promulgated pursuant thereto.
	The permittee shall not construct, reconstruct, or modify an affected facility without first having submitted a complete application and received a permit for the planned activity from the Division, except as provided in this permit or in 401 KAR 52:040, State-origin permits.
	Issuance of this permit does not relieve the permittee from the responsibility of obtaining other permits, licenses, or approvals that may be required by the Cabinet or other federal, state, or local agencies. [401 KAR 52:040]
T-3	SECTION B. ADMINISTRATIVE REQUIREMENTS. [401 KAR 52:040]
T-4	B1. The permittee shall comply with all conditions of this permit. Noncompliance shall be a violation of 401 KAR 52:040, Section 3(1)(b) and is grounds for enforcement action including but not limited to the termination, revocation and reissuance, or revision of this permit. [401 KAR 52:040 Section 3(1)(b)]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

# Narrative Requirements:

Condition	
No.	Condition
T-5	B2. Any condition or portion of this permit which becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this permit. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1a (11)]. [401 KAR 52:040 Section 23]
T-6	B3. This permit may be revised, revoked, reopened, reissued, or terminated for cause. The filing of a request by the permittee for any permit revision, revocation, reissuance, or termination, or of a notification of a planned change or anticipated noncompliance shall not stay any permit condition. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1a (4) and (5)]. [401 KAR 52:040 Section 23]
T-7	B4. This permit does not convey property rights or exclusive privileges. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1a, 8]. [401 KAR 52:040 Section 23]
T-8	B5. Nothing in this permit shall alter or affect the liability of the permittee for any violation of applicable requirements prior to or at the time of permit issuance. [401 KAR 52:040 Section 11(3)]
T-9	B6. This permit shall be subject to suspension at any time the permittee fails to pay all fees within 90 days after notification as specified in 401 KAR 50:038 Section 3(6)(b), Air emissions fee. The permittee shall submit an annual emissions certification. [401 KAR 52:040 Section 20]
T-10	B7. All previously issued construction and operating permits are hereby null and void. [401 KAR Chapter 52]
T-11	SECTION C. RECORD KEEPING REQUIREMENTS. [401 KAR 52:040]
T-12	C1. Records of all required monitoring data and support information, including calibrations, maintenance records, and original strip chart recordings, and copies of all reports required by the Division for Air Quality, shall be retained by the permittee for a period of at least five years and shall be made available for inspection upon request by any duly authorized representative of the Division for Air Quality. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Sections 1b (IV)(2) and 1a (7)]. [401 KAR 52:040 Section 23]
T-13	C2. The permittee shall perform compliance certification and recordkeeping sufficient to assure compliance with the terms and conditions of the permit. Documents, including reports, shall be certified by a responsible official. [401 KAR 52:040 Section 21]
T-14	SECTION D. REPORTING REQUIREMENTS. [401 KAR 52:040]

Page 4 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Narrative Requirements:

Condition	
No.	Condition
T-15	D1. a. The permittee shall notify the Regional Office listed on the front of this permit concerning startups, shutdowns, or malfunctions as follows i. When emissions during any planned shutdowns and ensuing startups will exceed the standards, notification shall be made no later than three (3) days before the planned shutdown, or immediately following the decision to shut down, if the shutdown is due to events which could not have been foreseen three (3) days before the shutdown.  ii. When emissions due to malfunctions, unplanned shutdowns and ensuing startups are or may be in excess of the standards notification shall be made as promptly as possible by telephone (or other electronic media) and shall submit written notice upon request.  b. The permittee shall promptly report deviations from permit requirements including those attributed to upset conditions (other than emission exceedances covered by Reporting Requirement condition D1.a above), the probable cause of the deviation, and corrective or preventive measures taken; to the Regional Office listed on the front of this permit within 30 days. Other deviations from permit requirements shall be included in the semiannual report. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1b, V(3)]. [401 KAR 50:055 Section 1]
T-16	D2. The permittee shall furnish information requested by the Cabinet to determine if cause exists for modifying, revoking and reissuing, or terminating the permit; or compliance with the permit. [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1a, 6]. [401 KAR 52:040 Section 23]
T-17	SECTION E. INSPECTIONS. [401 KAR 52:040]
T-18	E1. The permittee shall allow authorized representatives of the Cabinet to perform the following during reasonable times:  a. Enter upon the premises to inspect any facility, equipment (including air pollution control equipment), practice, or operation;  b. To access and copy any records required by the permit:  c. Inspect any facilities, equipment (including monitoring and pollution control equipment), practices, or operations required by the permit.  d. Sample or monitor substances or parameters to assure compliance with the permit or any applicable requirements.  Reasonable times are defined as during all hours of operation, during normal office hours; or during an emergency. [401 KAR 52:040 Section 3(1)(f)]
T-19	SECTION F. EMERGENCIES/ENFORCEMENT PROVISIONS. [401 KAR 52:040]
T-20	F1. The permittee shall not use as defense in an enforcement action, the contention that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance [Cabinet Provisions and Procedures for Issuing State Origin Permits, Section 1a, 3]. [401 KAR 52:040 Section 23]

Page 5 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Narrative Requirements:

Condition No.	Condition
	Condition
T-21	F2. An emergency shall constitute an affirmative defense to an action brought for the noncompliance with the technology-based emission limitations if the permittee demonstrates through properly signed contemporaneous operating logs or relevant evidence that:  a. An emergency occurred and the permittee can identify the cause of the emergency;  b. The permitted facility was at the time being properly operated;  c. During an emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements in the permit; and  d. The permittee notified the Division as promptly as possible and submitted written notice of the emergency to the Division within two working days after the time when emission limitations were exceeded due to the emergency and included a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.  These provisions are in addition to any emergency or upset provision contained in an applicable requirement. [401 KAR 52:040 Section 22(1)]
T-22	F3. In an enforcement proceeding, the permittee seeking to establish the occurrence of an emergency shall have the burden of proof. [401 KAR 52:040 Section 22(2)]
T-23	SECTION G. COMPLIANCE. [401 KAR 52:040]
T-24	G1. Periodic testing or instrumental or non-instrumental monitoring, which may consist of record keeping, shall be performed to the extent necessary to yield reliable data for purposes of demonstration of continuing compliance with the conditions of this permit. For the purpose of demonstration of continuing compliance, the following guidelines shall be followed:  a. Pursuant to 401 KAR 50:055, General compliance requirements, Section 2(5), all air pollution control equipment and all pollution control measures proposed by the application in response to which this permit is issued shall be in place, properly maintained, and in operation at any time an affected facility for which the equipment and measures are designed is operated, except as provided by 401 KAR 50:055, Section 1.  b. All the air pollution control systems shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers. A log shall be kept of all routine and non routine maintenance performed on each control device.  c. A log of the monthly raw material consumption and/or monthly production rates shall be kept available at the facility. Compliance with the emission limits may be demonstrated by computer program, spread sheets, calculations or performance tests as may be specified by the Division. [401 KAR 50:055 Section 2]
T-25	G2. Permit Shield - A permit shield shall not protect the owner or operator from enforcement actions for violating an applicable requirement prior to or at the time of permit issuance. Compliance with the conditions of this permit shall be considered compliance with all:  (a) Applicable requirements that are included and specifically identified in this permit; or  (b) Non-applicable requirements expressly identified in this permit. [401 KAR 52:040 Section 11]
T-26	SECTION H. CONSTRUCTION REQUIREMENTS. [401 KAR 52:040]

Page 6 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Narrative Requirements:

Condition No.	Condition
T-27	H1. Unless construction is commenced on or before 18 months after the date of issue of this permit, or if construction is commenced and then stopped for any consecutive period of 18 months or more, or is not completed within a reasonable timeframe then the construction and operating authority granted by this permit for those affected facilities for which construction was not completed shall immediately become invalid. Upon a written request, the cabinet may extend these time periods if the source shows good cause. [401 KAR 52:040 Section 12(3)]
T-28	H2. Unless notification and justification to the contrary are received by this Division, the date of achieving the maximum production rate at which the affected facilities will be operated shall be deemed to be 30 days after initial start-up. [401 KAR 59:005 Section 3(1)(b)]
T-29	H3. Operation of the affected facilities authorized by this permit shall not commence until compliance with applicable standards specified herein has been demonstrated in accordance with the requirements of 401 KAR 52:040, Section 12(4)(a) and (b). Until compliance is demonstrated, the source may only operate for the purpose of demonstrating compliance. [401 KAR 52:040 Section 12(4)(b)]
T-30	H4. If a demonstration of compliance, through performance testing was made at a production rate less than the maximum specified in the application form, then the permittee is only authorized to operate at a rate that is not greater than 110 percent of the rate demonstrated during performance testing. If and when the facility is capable of operation at the rate specified in the application, compliance must be demonstrated at the new production rate if required by the Division [Policy Manual of the Division for Air Quality, Section VII 1.(2 and 3)]. [401 KAR 50:016 Section 1(1)]

Page 7 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

AREA3 (EP3) Haul Road and Yard Constructed 1969:

Narrative Requirements:

Condition No.	Condition
T-1	No person shall cause or permit the discharge of visible fugitive dust emissions beyond the lot line of the property on which the emissions originate. [401 KAR 63:010 Section 3(2)]
T-2	No person shall cause, suffer, or allow any material to be handled, processed, transported, or stored; a building or its appurtenances to be constructed, altered, repaired, or demolished, or a road to be used without taking reasonable precaution to prevent particulate matter from becoming airborne. [401 KAR 63:010 Section 3(1)]
T-3	Such reasonable precautions shall include, when applicable, but not be limited to the following: use, where possible, of water or chemicals for the control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads or the cleaning of land. [401 KAR 63:010 Section 3(1)(a)]
T-4	Such reasonable precautions shall include, when applicable, but not be limited to the following: application and maintenance of asphalt, oil, water, or suitable chemicals on roads, material stockpiles, and othe surfaces which can create airborne dusts. [401 KAR 63:010 Section 3(1)(b)]
T-5	Such reasonable precautions shall include, when applicable, but not be limited to the following: installation and use of hoods, fans, or fabric filters to enclose and vent the handling of dusty materials, or the use of water sprays or other measures to suppress the dust emissions during handling. Adequate containment methods shall be employed during sandblasting or other similar operations. [401 KAR 63:010 Section 3(1)(c)]
T-6	Such reasonable precautions shall include, when applicable, but not be limited to the following: covering, at all times when in motion, open bodied trucks transporting materials likely to become airborne. [401 KAR 63:010 Section 3(1)(d)]
T-7	Such reasonable precautions shall include, when applicable, but not be limited to the following: the maintenance of paved roadways in a clean condition. [401 KAR 63:010 Section 3(1)(e)]
T-8	Such reasonable precautions shall include, when applicable, but not be limited to the following: the prompt removal of earth or other material from a paved street which earth or other material has been transported thereto by trucking or earth moving equipment or erosion by water. [401 KAR 63:010 Section 3(1)(f)]
T-9	The provisions of Section 3 (1) and (2) of this administrative regulation shall not be applicable to temporary blasting or construction operations. [401 KAR 63:010 Section 4(3)]
T-10	No one shall allow earth or other material being transported by truck or earth moving equipment to be deposited onto a paved street or roadway. [401 KAR 63:010 Section 4(4)]

Page 8 of 20

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 9 of 20

## **COMB2 (EP 5) Wood Waste Boiler**

# Max. Capacity - 15.1 Million British Thermal Units per hour (mmBtu/hr)

# Limitation Requirements:

Condition		
No.	Parameter	Condition
L-1	SO2 (Sulfur Dioxide)	The unit shall have emissions of SO2 (Sulfur Dioxide) <= 4.16 lb/mm Btu actual heat input.
		Compliance Demonstration
		Continual compliance with the SO2 standard is demonstrated, based on AP-42, Table 1.6-2 emission factor of .025 lb/mmBtu, for dry wood-fired boilers. [401 KAR 59:015 Section 5(1)] This requirement is applicable during the following months: All Year. Statistical basis: Three-hour average.
L-2	PT (Particulate Matter)	The unit shall have emissions of PT (Particulate Matter) <= .50 lb/mm Btu actual heat input.
		Compliance Demonstration
		Continual compliance with the PT standard is demonstrated, based on AP-42, Table 1.6-1 emission factor of .30 lb/mmBtu, for dry wood-fired boilers. [401 KAR 59:015 Section 4(1)] This requirement is applicable during the following months: All Year. Statistical basis: Three-hour average.
L-3	Visible Emissions	The unit shall have Visible Emissions <= 20 % opacity except for emissions occurring during cleaning of the firebox, blowing of soot and building of a new fire. [401 KAR 59:015 Section 4(2)] This requirement is applicable during the following months: All Year. Statistical basis: Six-minute average.
L-4	Visible Emissions	While cleaning of the fire box or blowing of soot is being done, Visible Emissions <= 40 % opacity shall be permitted for not more than 6 consecutive minutes in any 60 consecutive minutes. [401 KAR 59:015 Section 4(2)] This requirement is applicable during the following months: All Year. Statistical basis: Six-minute average.

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 10 of 20

1	lon	itor	inσ	Rec	nire	ments:
IV	1011	1001	шц	VCC	unci	memes.

	ring Requirements	S.		
No.	Parameter	Condition		
M-1	fuel	The amount of each combusted fuel monitored by approved method(s) daily shall be determined for the unit. [401 KAR Chapter 52 Section 10] This requirement is applicable during the following months: All Year. Statistical basis: Instantaneous determination.		
Narrati	ve Requirements:			
App	licable Regulations:			
Condition	1			
No.	Condition			
T-1	Applicable Regulatio KAR 59:015]	ons: New Indirect Heat Exchangers applies to new affected facilities less than 250 million Btu/hr commenced on or after April 9, 1972. [401		
T-2	Generating Units, for	Applicable Regulations: Incorporating by reference 40 CFR 60 Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units, for emission units that have a maximum heat input capacity of 100 million Btu/hr or less, but greater than or equal to 10 million Btu/hr for which construction commenced after June 9, 1989. [401 KAR 61:005 Section 3(e)]		
Add	itional Limitations:			
Condition	1			
No.	Condition			
T-3		Additional Limitations: While building a new fire there is no applicable opacity limit on visible emissions from the unit provided the manufacturer recommended method is used to build the fire and the manufacturer recommended time frame for bringing the boiler up to operating conditions is not exceeded. [401 KAR 59:01 Section 4(2)]		
Reco	ordkeeping:			

Condition No.	Condition
T-4	Recordkeeping: Record the ash content of the fuel when monitored. [401 KAR Chapter 52 Section 10]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 11 of 20

3 T	-	•	
Narrative	1200	1111404	nantai
INALIALIVE	$r \vdash \iota$		1161118
1 1411411 0	100	MII OI	moment.

### Recordkeeping:

T-6

	1 6
Condition	
No.	Condition
T-5	Recordkeeping: Record the heating value of the fuel when monitored. [401 KAR Chapter 52 Section 10]
Monitoring:	
Condition	
No.	Condition

Monitoring: The permittee shall perform a qualitative visual observation of the opacity of emissions from the stack on a weekly basis and maintain a log of the observations. If visible emissions are seen (not including condensed water vapor within the plume) from the stack, then the opacity shall be determined by Reference Method 9. If the emissions are in excess of the applicable opacity limit, then an inspection shall be initiated of the control equipment for any necessary repairs. [401 KAR Chapter 52 Section 10]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 12 of 20

# GACT1 (EP1) Woodworking Operations Chip Bagger(MP2) & Screen Separator(MP4)

# Limitation Requirements:

Condition		
No.	Parameter	Condition
L-1	PT (Particulate Matter)	Each unit shall have emissions of PT (Particulate Matter) <= 2.90 lbs/hr
		Compliance Demonstration
		Compliance will be demonstrated from the following emission calculation basis and monitoring requirements: PT emission in pounds per hour= (monthly processing rate in tons/month)(1 month/hours of operation that month)(emission factor of 1.0 lb PT/ton)(1-control efficiency of .70).
		See Monitoring Requirements for monitoring rates and visual inspection of controls. [401 KAR 59:010 Section 3(2)] Statistical basis: Three-hour average.
L-2	Visible Emissions	Each unit shall have Visible Emissions < 20 % opacity. [401 KAR 59:010 Section 3(1)] Statistical basis: Six-minute average.
Narrativ	re Requirements:	
Appli	cable Regulations:	
Condition		
No.	Condition	
T-1	Applicable Regulations: New process operations is applicable to each affected facility associated with a process operation commenced after July 2, 1975 and limits particulate emissions. [401 KAR 59:010]	

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 13 of 20

# Narrative Requirements:

### Recordkeeping:

Condition No.	Condition
T-2	Recordkeeping: The permitee shall maintain records of the following: 1) monthly hours of operation and material processing rate; 2) the weekly log of qualitative visual observation of opacity of emissions and the opacity determined by Reference Method 9, if any were taken, and repairs that were made due to any opacity reading which exceeded the standard. [401 KAR Chapter 52 Section 10]
Monit	coring:
Condition	C - 1141 - 11

Condition No.	Condition
T-3	Monitoring: The permittee shall monitor the amount of material processed on a monthly basis. [401 KAR Chapter 52 Section 10]
T-4	Monitoring: The permittee shall monitor the hours of operation of the unit on a monthly basis. [401 KAR Chapter 52 Section 10]
T-5	Monitoring: The permittee shall perform a qualitative visible observation of the opacity of emissions from each stack on a weekly basis and maintain a log of the observation. If visible emission from a stack are seen, then the opacity shall be determined by EPA Reference Method 9 and an inspection shall be initiated for any necessary repairs. [401 KAR Chapter 52 Section 10]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 14 of 20

# GACT2 (EP1) Woodworking Operation Two (2) Grinder/Shredders (MP6) & Four (4) Chip Trailers (MP7)

# Limitation Requirements:

Conditio	n		
No.	Parameter	Condition	
L-1	PT (Particulate Matter)	Each unit shall have emissions of PT (Particulate Matter) <= 2.34 lbs/hr Compliance Demonstration	
		Compliance will be demonstrated from the following emission calculation basis and monitoring requirements: PT emission in pounds per hour= (monthly processing rate in tons/month)(1 month/hours of operation that month)(emission factor of 9.1lb PT/ton)(1-control efficiency of 0.99).	
		See Monitoring Requirements for monitoring rates and visual inspection of controls. [401 KAR 59:010 Section 3(2)] Statistical basis: Three-hour average.	
L-2	Visible Emissions	Each unit shall have Visible Emissions < 20 % opacity. [401 KAR 59:010 Section 3(1)] Statistical basis: Six-minute average.	
	ve Requirements:		
Conditio			
No.	Condition		
T-1		Applicable Regulations: New process operations is applicable to each affected facility associated with a process operation commenced after July 2, 1975 and lim particulate emissions. [401 KAR 59:010]	
Rec	ordkeeping:		
Conditio	n		
No.	Condition		
T-2	visual observation of opacity	the shall maintain records of the following: 1) monthly hours of operation and material processing rate; 2) the weekly log of qualitative of emissions and the opacity determined by Reference Method 9, if any were taken, and repairs that were made due to any opacity standard. [401 KAR Chapter 52 Section 10]	

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 15 of 20

# Narrative Requirements:

### **Monitoring:**

Condition No.	Condition
T-3	Monitoring: The permittee shall monitor the amount of material processed on a monthly basis. [401 KAR Chapter 52 Section 10]
T-4	Monitoring: The permittee shall monitor the hours of operation of the unit on a monthly basis. [401 KAR Chapter 52 Section 10]
T-5	Monitoring: The permittee shall perform a qualitative visible observation of the opacity of emissions from each stack on a weekly basis and maintain a log of the observation. If visible emission from a stack are seen, then the opacity shall be determined by EPA Reference Method 9 and an inspection shall be initiated for any necessary repairs. [401 KAR Chapter 52 Section 10]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 16 of 20

# **GACT3 (EP1) Milling Operations (MP1) Constructed 1992:**

# Limitation Requirements:

Condition		
No.	Parameter	Condition
L-1	PT (Particulate Matter)	Each unit shall have emissions of PT (Particulate Matter) <= 7.84 lbs/hr
		Compliance Demonstration
		Compliance will be demonstrated from the following emission calculation basis and monitoring requirements: PT emission in pounds per hour= (monthly processing rate in tons/month)(1 month/hours of operation that month)(emission factor of 6.0 lb PT/ton)(1-control efficiency of 0.99).
		See Monitoring Requirements for monitoring rates and visual inspection of controls. [401 KAR 59:010 Section 3(2)] Statistical basis: Three-hour average.
L-2	Visible Emissions	Each unit shall have Visible Emissions < 20 % opacity. [401 KAR 59:010 Section 3(1)] Statistical basis: Six-minute average.
Narrativ	e Requirements:	
Appli	cable Regulations:	
Condition		
No.	Condition	
T-1	Applicable Regulations: New particulate emissions. [401 K	w process operations is applicable to each affected facility associated with a process operation commenced after July 2, 1975 and limits KAR 59:010]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 17 of 20

# Narrative Requirements:

### Recordkeeping:

Condition No.	Condition
T-2	Recordkeeping: The permitee shall maintain records of the following: 1) monthly hours of operation and material processing rate; 2) the weekly log of qualitative visual observation of opacity of emissions and the opacity determined by Reference Method 9, if any were taken, and repairs that were made due to any opacity reading which exceeded the standard. [401 KAR Chapter 52 Section 10]
Monit	oring:
Condition	

Condition No.	Condition
T-3	Monitoring: The permittee shall monitor the amount of material processed on a monthly basis. [401 KAR Chapter 52 Section 10]
T-4	Monitoring: The permittee shall monitor the hours of operation of the unit on a monthly basis. [401 KAR Chapter 52 Section 10]
T-5	Monitoring: The permittee shall perform a qualitative visible observation of the opacity of emissions from each stack on a weekly basis and maintain a log of the observation. If visible emission from a stack are seen, then the opacity shall be determined by EPA Reference Method 9 and an inspection shall be initiated for any necessary repairs. [401 KAR Chapter 52 Section 10]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 18 of 20

# GACT4 (EP 4) Gluing Operations (EP 4) Constructed 1992:

Narrative Requirements:

Condition No.	Condition
T-1	Persons responsible for a source from which hazardous matter or toxic substances may be emitted shall provide the utmost care and consideration, in the handling of these materials, to the potentially harmful effects of the emissions resulting from such activities. No owner or operator shall allow any affected facility to emit potentially hazardous matter or toxic substances in such quantities or duration as to be harmful to the health and welfare of humans, animals and plants. Evaluation of such facilities as to adequacy of controls and/or procedures and emission potential will be make on an individual basis by the cabinet. [401 KAR 63:020 Section 3]

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 19 of 20

# GACT5 (EP1) Wood Storage Silos Chip Holding(MP2) & Wood-Waste Boiler(MP5) Silos

# Limitation Requirements:

Condition			
No.	Parameter	Condition	
L-1	PT (Particulate Matter)	Each unit shall have emissions of PT (Particulate Matter) <= 2.90 lbs/hr	
		Compliance Demonstration	
		Compliance will be demonstrated from the following emission calculation basis and monitoring requirements: PT emission in pounds per hour= (monthly processing rate in tons/month)(1 month/hours of operation that month)(emission factor of 1.0 lb PT/ton)	
		See Monitoring Requirements for monitoring rates and visual inspection of controls. [401 KAR 59:010 Section 3(2)] Statistical basis: Three-hour average.	
L-2	Visible Emissions	Each unit shall have Visible Emissions < 20 % opacity. [401 KAR 59:010 Section 3(1)] Statistical basis: Six-minute average.	
Narrativ	e Requirements:		
Applio	Applicable Regulations:		
Condition			
No.	Condition		
T-1	Applicable Regulations: New particulate emissions. [401 K.	process operations is applicable to each affected facility associated with a process operation commenced after July 2, 1975 and limits AR 59:010]	

Twelve Oaks Millwork Facility Requirements

Activity ID No.: APE20040001

Page 20 of 20

# Narrative Requirements:

### Recordkeeping:

Condition No.	Condition
T-2	Recordkeeping: The permitee shall maintain records of the following: 1) monthly hours of operation and material processing rate; 2) the weekly log of qualitative visual observation of opacity of emissions and the opacity determined by Reference Method 9, if any were taken, and repairs that were made due to any opacity reading which exceeded the standard. [401 KAR Chapter 52 Section 10]
Monitoring:	
Condition	C 1/4

Condition No.	Condition
T-3	Monitoring: The permittee shall monitor the amount of material processed on a monthly basis. [401 KAR Chapter 52 Section 10]
T-4	Monitoring: The permittee shall monitor the hours of operation of the unit on a monthly basis. [401 KAR Chapter 52 Section 10]
T-5	Monitoring: The permittee shall perform a qualitative visible observation of the opacity of emissions from each stack on a weekly basis and maintain a log of the observation. If visible emission from a stack are seen, then the opacity shall be determined by EPA Reference Method 9 and an inspection shall be initiated for any necessary repairs. [401 KAR Chapter 52 Section 10]